

JABRA BIZ 1500 QD/USB

- Strong durability
- All day wearing comfort
- Flexible (bendable) microphone boom arm construction
- Noise cancelling microphone



Jabra®

| FEATURES | DESCRIPTION |
|----------------------------------|---|
| Packaging dimensions | Master carton:600*399*316mm Sales box (Plastic bag) Size (L x W x H) in cm: 18 x 23 x 2. In inches: 7,08 x 9,05 x 0,78 |
| Main unit dimension | Headset: L131*H165*W57 |
| Weight mono / duo with cord | Mono QD: 88 gram. In ounce: 3,10. Pound 0,19 Duo QD: 115 gram. In ounce: 4,05. Pound 0,25 Mono USB: 119,5. In ounce 4,21. Pound 0,26 Duo USB: 146 gram. In ounce 5,14. Pound 0,32 |
| Weight mono / duo without cord | Mono QD: 48 gram. In ounce 1,69. Pound 0,11 Duo QD: 74 gram. In ounce 2,61. Pound 0,16 Mono USB: 48 gram. In ounce 1,69. Pound 0,11 Duo USB: 74 gram. In ounce 2,61. Pound 0,16 |
| Whats in the box | Warranty card, warning card, Quick start guide, Headset |
| Certifications | CE, FCC, UL, cUL, EAC, RCM, KCC, RoHS, REACH |
| Warranty | 2 year |
| Headset bandwidth | Wideband |
| Material used | Headband housing, outer, inner & Controller Front/Back housing: PC/ABS, Earfoam: SS-55C, Micphone housing: Luran Flexboom arm: PA, Speaker housing: PC/ABS |
| Features | QD & USB: Noise cancel microphone, Flexible (bendable) microphone boom arm construction, Foam ear cushion(s). Leatherette(s) available as extra accessory, All day wearing comfort, Strong durability. QD: Hybrid wideband speaker for QD (up to 4.500 Hz) USB: Acoustic protection PeakStop, True wideband/HD speaker for USB (up to 6.800 Hz), USB Solution supported by Jabra Direct and Jabra Xpress. USB controller: Volume up/down, Mute on/off. |
| Speaker Max Input Power | 30mW |
| Speaker, user hearing protection | Jabra PeakStop™ 118 dBA SPL (RMS) |
| Microphone Frequency Range | 1-5kHz |
| Microphone bandwidth | 1-5kHz |
| Microphone type | Uni-Directional Microphone |
| Power consumption microphone | Current Consumption 70-150µA@RL=3.9kΩ, Vs=3.0V |

| FEATURES | QD CONNECTIVITY DESCRIPTIONS | USB CONNECTIVITY DESCRIPTIONS |
|---------------------------------|---|--|
| Connection (mini jack, USB, QD) | QD | USB |
| Speaker Size | 32x8mm | 32x7.6mm |
| Speaker sensitivity | 115.5dB±3dB/1mW At 1000Hz | 102dB±3dB/1mW At 1000Hz |
| Speaker impedance | Duo:150Ω±15%/1000Hz/1.0V Mono:300Ω±15%/1000Hz/1.0V | 32Ω±15%/1000Hz/1.0V |
| Speaker Frequency Range | 20Hz-4.5kHz | 20Hz-6.8kHz |
| Speaker bandwidth Music mode | 20Hz-4.5kHz | 20Hz-6.8kHz |
| Speaker bandwidth Speak mode | 20Hz-4.5kHz | 20Hz-6.8kHz |
| Microphone Sensitivity | -32 to -28 dB@f=1kHz, Pin=1Pa, 0dB=1V/Pa | -35 to -31 dB@f=1kHz,Pin=1Pa,0dB=1V/Pa |
| Cord length | 95cm | 230cm |

| ITEM NUMBER | DESCRIPTION | EAN | UPC |
|-------------|--------------------------|---------------|--------------|
| 1513-0154 | BIZ 1500 Mono QD EMEA | 5706991018974 | N/A |
| 1513-0157 | BIZ 1500 Mono QD NA/APAC | 5706991018981 | 706487013150 |
| 1519-0154 | BIZ 1500 Duo QD EMEA | 5706991018998 | N/A |
| 1519-0157 | BIZ 1500 Duo QD NA/APAC | 5706991019001 | 706487013167 |
| 1553-0159 | BIZ 1500 Mono USB | 5706991019018 | 706487013174 |
| 1559-0159 | BIZ 1500 Duo USB | 5706991019025 | 706487013181 |

* Phone dependent